

## TURNER Light Duty Under Counter Lathe Machine

## STANDARD ACCESSORIES:

- ► Four Position Tool Post
- ► Motor Pulley
- ▶ Drive V Belt
- ▶ Dead Centre (2 Nos.)
- ► Centre Adaptor
- ► Tool Post Key
- ► Chuck Plate
- ► Change Gear Set (Inch & mm)



TECHNICAL SPECIFICATION	
SPECIFICATION	ML - 1
BED:	
Bed Type	2 V & 2 Flat
Bed Length	1375 (4'6")
Bed Width	240 (9 ½")
Gap Length	110 mm
CAPACITY:	
Height of Centre	175 mm (7")
Swing Over Bed	350 mm
Swing Over Gap	535 mm
Swing Over Cross Slide	200 mm
Admit Between Centre	650 mm
Movement of Cross Slide	200 mm
Movement of Compound Slide	115 mm
MAIN SPINDLE :	
Spindle Nose (Threaded type)	Ø 62 mm
Taper Bore in Spindle Sleeve	MT - 3
Spindle Bore	Ø 40 mm
TAIL STOCK :	
Quill Dia.	Ø 38.1 mm
Taper in Quill	MT - 3
Quill Travel	120 mm
SPEED:	
No. of Spindle Speed	8
RPM (Low/High)	35-1000
THREADS:	
Metric Thread	13 (1 to 6 mm
English Thread	19 (2 to 24 TP
Lead Screw	Ø 1" x 4 TPI
ELECTRICALS:	
Motor Power	1 HP / 0.745 k
DRIVE:	
V Belt	B - 60
GENERAL:	
Weight (Approx.)	550 Kg.
Floor Space Occupied in (mm)	1600x700x137
(Approx.) L x W x H	

<sup>\*</sup> Above mentioned information is subject to change because of Product Improvement.

<sup>\*</sup> All the Parts shown in photo are not included in Standard Accessories.