

## Universal Horizontal Gear Head Milling Machine MAC - 2

## STANDARD ACCESSORIES:

- ► Hardened & Ground Arbor with Studs & Collars
- ► Electric panel board (Hanging Type)
- ► Spindle Lock Limit Switch
- ► Operating Handle
- ► Motor Pulley



TECHNICAL SPECIFICATION	
SPECIFICATION	MAC - 2
TABLE :	_
Table Length x Width Clamping Area 'T' - Slot Number Centre Distance Size (Width)	1100 mm x 280 mm 925 mm x 280 mm 3 70 mm 18 mm
AXIS TRAVEL :	
Longitudinal Travel Vertical Travel Vertical Travel After Mounting Vertical Attachment Transverse Travel	700 mm 500 mm 385 mm
FEED:	260 mm
No. of Feeds	
Range of Feeds	4
MAIN SPINDLE :	13.74/19.25/26.75/44.50 mm/min
Spindle Nose Taper No. of Speeds Speeds Range Spindle Bore Arbor Dia.	ISO 40 8 45 - 830 rpm Ø 22 mm Ø 25.4 mm
POWER:	
Main Motor Coolant Pump Motor	2 HP 1.5 kw/1440 rpm 0.11 kw/2700 rpm
WORKING RANGE :	
Swivel of Table Distance between Spindle	± 45 Degree
Axis to Table Surface Distance of Spindle Axis to	500 mm
bottom Surface of over Arm	135 mm
Coolant Tank Capacity  GENERAL:	15 Liters
Weight (Approx.)	1100 K-
Floor Space Occupied (Apporx) L x W x H	1400 Kg 1400x1570x1800 mm

<sup>\*</sup> Above mentioned information is subject to change because of Product Improvement.

<sup>\*</sup> All the Parts shown in photo are not included in Standard Accessories.